

Remotely Control Your Computer.



CAT5•5000HD

The ex•ten•it CAT5•5000HD extends your dual DVI displays and USB up to 150 feet away from your DVI or HDMI source.

How it works

The CAT5•5000HD sender unit sits next to your computer. The cables supplied with the CAT5•5000HD connects your DVI source(s) and USB to the send unit. The CAT5•5000HD receiver unit sits next to your DVI displays - up to 150 feet away. The displays and USB plug into the back of the CAT5•5000HD receiver unit. Four CAT-5 cables connect the CAT5•5000HD-S and the CAT5•5000HD-R units to each other.

The CAT5•5000HD is HDCP compliant.

Package Includes:

- the CAT5•5000HD-S
- the CAT5•5000HD-R
- Two 6 foot DVI to HDMI cables
- One 6 foot USB cable
- Two 5V Power Supply
- User's Manual

Features:

- Uses CAT-5 cable for DDC and control signals
- Extends any DVI (Digital Video Interface) compliant device up to 150 from the computer
- Extends USB 1.1 compliant devices up to 150 from the computer
- Saves space on your desktop Increases productivity
- Eliminates computer noise where you work
- Supports VESA Standard resolutions and HDTV resolution
- Supports DDWG standard for DVI compliant monitors
- Installs in minutes

Specifications:

- Video Amplifier Bandwidth: 1.65 GHz
- Single Link Range: 1080P/1920 x 1200
- HDCP Compliant
- Input Video Signal: 1.2 volts p-p
- Input DDC Signal: 5 volts p-p (TTL)
- Video HDMI Input Connector: 19 pin Type A
- Video DVI Output Connector: DVI-I (29 pin) female, Supports ONLY Digital Signals
- USB Input: USB type "B" Connector
- USB Output: Two USB type "A" connectors
- Link Connector: RJ-45
- Power Supply: 5V DC (External)
- Power Consumption: 15 Watts (max)
- Dimensions: (8.4" in./213.36mm) W x (1.75" in./44.45mm) H x (4.4" in./111.76mm) D
- Shipping Weight: 7lbs.

***Note:** For distances over 100 ft. shielded CAT-5 cable for video is recommended for optimal video quality. The DDC CAT-5 cable does not need to be shielded.

GE-EXT-CAT5-5000HD